

Oil Fill Point Cabinets



Description

Many installations require the filling point for oil storage tanks to be enclosed in a lockable cabinet housed within the fabric of the building or built into a boundary wall to limit access to authorised personnel only. This is easy to achieve by using the Landon Kingsway Fillpoint Cabinet.

The Landon Kingsway Fillpoint Cabinet conforms with metric brickwork and is available as a standard unit in single, double and triple sizes. The Fillpoint Cabinet can be fitted with screwdown stop valves up to 100mm in diameter, each complete with its own captive dust cap, with lockable versions available as an option.

Cabinet Construction

The entire cabinet is constructed from 16 SWG mild steel, coated with a protective aluzinc finish and is provided with grouting strips for building into exterior fabric.

Cabinets are supplied with a grey epoxy powder coating. A shatter proof polycarbonate viewing window is provided as standard for easy reading. Contents gauges are supplied as an extra. Studs are pre installed to accept 150mm gauges and the Landon Kingsway Filguard Alarm Panel. Holes are pre drilled to accept Fill Valve assemblies. Internal lighting with automatic switching is also available as an option. The door is completely weather sealed. A supporting gas strut eases opening and closing and maintains a fully open position when required.

Models in the Range

A Type Cabinet – one fill valve

B Type Cabinet – two fill valves

C Type Cabinet – three fill valves

Available with or without viewing window

Oil Fill Valve Assemblies

25mm

50mm

65mm

80mm

100mm

Optional Extras

- Filguard High Level Alarm Panel
- Filguard Float Sensing Unit
- Flameproof Float Sensing Unit
- Capacitance Level Controls
- Contents Gauges
- Lighting & Switching Assembly
- Fill Valve Assembly

Special Features

- Conforms With Metric Brickwork
- Door & Frame Coated in Aluzinc Then Finished In Polyester Powder Finish
- Polycarbonate Vandal Proof Window
- Gas Filled Support Strut
- Lockable Door To Restrict Access
- Accommodates 25mm, 50mm 65mm 80mm and 100mm Fill Valves (Conforming to BS 799 Part 1)
- Non Standard Versions Available To Customers Own Specifications
- Stainless Steel Versions Available To Special Order